

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claims 1-10. (Canceled)

11. (Previously presented) Motor vehicle (1) with an automobile body (6), which includes two rigid automobile body regions (3) located on both sides above side window regions (2), wherein, in a closed roof position, at least two panel-shaped roof sections (P1; P2) lie one after the other between the two rigid automobile body regions (3), can be moved relative to the lateral automobile body sections (3), and can be moved out of the closed position into an open position further below in the automobile body (6), wherein, from the closed position of the roof sections (P1; P2), at least a front roof section (P1) can be moved over a rear roof section (P2) that is located behind it by guiding it laterally in the manner of a sliding sunroof; wherein front end regions (P11) of the roof sections (P1; P2) can be raised from this position, and the roof sections (P1; P2), with

front ends (P11) thereof raised, can be lowered into the automobile body (6), wherein the roof section (P2) covered by the front roof section (P1) in the open sunroof position is guided in a guide rail (P6) during the downward movement into the automobile body (6) only in its rear half opposite the direction of vehicle travel (F); a roof section (P2) covered by the front roof section (P1) in an open sunroof position is guided in a guide rail (P6) during the downward movement into the automobile body (6) only in a rear half thereof opposite the direction of vehicle travel (F) and that, in the closed position of the roof sections (P1; P2), a rear window (H4), which can be separately moved between an open position and a closed position, borders directly on the rear roof section (P2).

12. (Previously presented) Motor vehicle (1) in accordance with Claim 11, wherein the front roof section (P1) is arranged as a roof section following behind a windshield frame (4).

13. (Previously presented) Motor vehicle (1) in accordance with Claim 11, wherein each of the roof sections (P1; P2) extends at least 40 centimeters in the longitudinal direction of the vehicle.

14. (Previously presented) Motor vehicle (1) in accordance with Claim 11, wherein the roof sections (P1; P2) are essentially transparent.

15. (Previously presented) Motor vehicle (1) in accordance with Claim 11, wherein in its closed position, the rear window (H4) is held in an essentially U-shaped opening of a hatch (H1) and is at least partially surrounded by the sides (H3) and lower edge (H2) of the hatch (H1).

16. (Currently amended) Motor vehicle (1) in accordance with Claim 11, wherein the rear window (H4) and the roof ~~other panel~~ sections (P1; P2) lie parallel to one another in the open position.

17. (Currently amended) Motor vehicle (1) in accordance with Claim 15, wherein during the opening of the hatch (H1), the forwardmost region (H5) of the hatch (H1) can be displaced rearward, ~~i.e.,~~ in the direction opposite the direction of vehicle travel, and during this displacement, the hatch (H1) frees a passage space (D1), which is covered when the hatch (H1) is closed, to allow the ~~front~~ roof sections (P1; P2) to be moved into the automobile body.

18. (Currently amended) Motor vehicle (1) in accordance with Claim 17, wherein in the closed state of the hatch (H1), the sides ~~lateral frame parts~~ (H3) are in alignment with automobile body regions (3) of the vehicle (1) that are positioned above side windows (2), which body regions (3) include at least the roof rails[[,]] and immediately follow the sides ~~frame parts~~ (H3) in the direction of vehicle travel (F), ~~and run above side windows (2)~~.

19. (Currently amended) Motor vehicle (1) in accordance with Claim 18, wherein the passage space (D1) is widened relative to a ~~the~~ clear width (D3) between the roof rails (3) in the transverse direction of the vehicle.